

### NORTHERN TESTING LABORATORIES, INC.

3330 INDUSTRIAL AVENUE 8005 SCHOON STREET POUCH 340043 FAIRBANKS, ALASKA 99701 ANCHORAGE, ALASKA 99518 PRUDHOE BAY, ALASKA 99734 (907) 456-3116 • FAX 456-3125 (907) 349-1000 • FAX 349-1016 (907) 659-2145 • FAX 659-2146

July 12, 2001

**U.S. Environmental Protection Agency** 

Attn: Kristine Karlson 1200 Sixth Avenue Seattle, WA 98101

Re: NPDES Permit AK-002139-3, Williams Alaska Petroleum, Inc., Industrial Compliance Monitoring and Inspection Report

Dear Ms. Karlson:

Enclosed are the completed results for the Williams Alaska Petroleum, Inc. industrial compliance monitoring and inspection samples collected on May 23, 2001 as required semiannually in section I.B. of NPDES Permit AK-002139-3. Gerald Voigt, Corporate Quality Assurance Manager (NTL), performed an evaluation of the sulfolane analysis and his report is also included. Samples were collected by Marylou Richard of NTL and Kelly Dygert of Williams Alaska Petroleum, and witnessed by Michael Pollen of NTL, Randy Johnson of the City of North Pole, and Dave Guinn of Williams Alaska Petroleum. The following table lists the sample collection methods:

<u>Parameter</u>	<b>Units</b>	Type of Sample
Flow	gpd	Recording flow meter
Oil & Grease	mg/L	Grab
Ammonia (as N)	mg/L	24-hour flow proportioned composite
TSS	mg/L	24-hour flow proportioned composite
BOD5	mg/L	24-hour flow proportioned composite
COD	mg/L	24-hour flow proportioned composite
BTEX	μg/L	Grab
Conductivity	µmhos/cm	Grab
pН	pH units	Grab
Metals	mg/L	24-hour flow proportioned composite

Results for flow, conductivity and pH tests are presented in Table 1.

Equipment Inspection: Aerated lagoon Cell A appeared to have a good air pattern. A section of the floating baffle curtain is detached from the anchors and is floating in the cell. Two air blowers are on-line, however dissolved oxygen is still approximately 0.1 mg/L. Hydrogen peroxide is being injected into the crossover between Cells A and C to increase the oxygen concentration and help reduce sulfolane levels. Water levels in all of the lagoon

Kristine Karlson, U.S. EPA July 12, 2001 Page 2

cells have been raised in an effort to increase detention time and slow the effluent flow to the City of North Pole.

Aerated lagoon Cell B is still isolated from the flow path and full of wastewater containing high concentrations of sulfolane. During the inspection on June 22, 2000, it was noted that Cell B had three "whales", or floating sections of liner, indicating air was being discharged under the liner. The whales are still present in the lagoon Cell B.

Cell C, from which the effluent discharges to the City of North Pole was full and the curtain baffles intact. A photo log of the equipment inspection and sample collection is enclosed with this report.

Table 1
Williams Alaska Petroleum Effluent Monitoring: 05/24/01 On Site Data

<u>Parameter</u>	<u>Units</u>	Result *	Instrument or Method
Flow	gpd	85,536	Flow Monitor **
Conductivity	μmhos/cm	9,400	Hach conductivity meter
pН	pH units	7.8	Corning pH meter
Temperature	°C	22.2	Corning pH meter

<sup>\*</sup> NTL reported values, shown in bold type, were read within one hour of sample collection using instruments at the North Pole Lagoon monitoring laboratory.

To help determine the relative precision of the analysis of these samples, selected data from the Williams laboratory and NTL laboratory were compared. These data comparisons and the relative percent difference (RPD) between these results are presented in Table 2.

Table 2
Comparative Data from Williams and NTL Labs on 5/23/2001 samples

Parameter	NTL Result	Williams Result	Relative % Diff.
Ammonia (as N), mg/L	29	22.25*	<b>26%</b>
Arsenic, mg/L	0.036	0.033	9%
BOD, 5-Day, mg/L	310	236	<b>2</b> 7%
COD, mg/L	660	640	3%
Conductivity, µmhos/cm	9,400	8,951	5%
pH, pH units	7.8	7.8	0%
TSS, mg/L	<b>4</b> 1	50	20%
Zinc mg/L	0.06	0.047	24%

<sup>\*</sup> Reported in Second Quarter 2001 Wastewater Compliance Report, 5/31/01.

NORTHERN TESTING LABORATORIES, INC.

<sup>\*\*</sup> Refinery control room meter reading = 59.4 gpm x 1,440 minutes/day.

Kristine Karlson, U.S. EPA July 12, 2001 Page 3

Not all trace metals were compared since nearly all of the data from both labs were below the method detection limits for those analyses.

The RPD data show that for most parameters, the comparability is good (within 10 - 25%). NTL reported a benzene result of 0.40  $\mu$ g/L while Williams reported non-detect for BTEX parameters. Both are well below the regulatory limit of 100  $\mu$ g/L.

The biological oxygen demand (5-day) results from both laboratories exceed the pretreatment permit limit of 200 mg/L. This is likely due to high sulfolane levels reported in a June 25, 2001 letter from Williams Alaska Petroleum, Inc. to Sharon Wilson of the U.S. Environmental Protection Agency. From April 23 to May 28, 2001, sulfolane concentrations were well above 100 mg/L. All other parameters were found to be within the pretreatment permit limits. Please call me at 907-456-3116 if you have any questions regarding this report.

Sincerely,

Northern Testing Laboratories, Inc.

Marylou Richard, Environmental Consultant

**Enclosures:** 

Photo Log

Sulfolane Analysis Evaluation

**NTL Data Transmittals** 

Chain of Custody/Work Order

cc: John Cherry, Williams Alaska Petroleum, Inc.

Kathleen McCullom, Williams Alaska Petroleum, Inc.

Dave Guinn, Williams Alaska Petroleum, Inc.

Kelly Dygert, Williams Alaska Petroleum, Inc.

Randy Johnson, City of North Pole

Tim Wingerter, ADEC Northern Regional Office

### Williams Alaska Petroleum, Inc. Industrial Compliance Inspection May 23, 2001



A section of the floating baffle curtain has come loose from the anchor blocks (left center in photo).



Floating section of liner, "whale", in Cell B. Flow to this cell is still being by-passed and stores wastewater containing high concentrations of sulfolane.



Lagoon Cell C, like A and B, are nearly filled to capacity. This is primarily due to the decrease in flow of wastewater to the City of North Pole containing elevated sulfolane concentrations.



Hydrogen peroxide is being injected between Cells A and C to raise dissolved oxygen levels and reduce sulfolane concentrations.



Marylou Richard (NTL) and Kelly Dygert (Williams) prepare containers and labels for an effluent sample while Dave Guinn (Williams) and Randy Johnson (City of North Pole) observe,



Marylou Richard (NTL) collects a BTEX sample.



## NORTHERN TESTING LABORATORIES, INC

3330 INDUSTRIAL AVENUE 5761 SILVERADO WAY; UNIT N POUCH 340043 FAIRBANKS, ALASKA 99701 ANCHORAGE, ALASKA 99518 PRUDHOE BAY, ALASKA 99734 (907) 456-3116 • FAX 456-3125 (907) 349-1000 • FAX 349-1016 (907) 659-2145 • FAX 659-2146

Williams Alaska Petroleum, Inc.

1100 H & H Lane North Pole, AK 99705

Attn:

Dave Guinn

Phone:

(907) 488-0054

Fax:

COC #:

26463

NTL Lab#:

F203966

Sample Matrix:

Wastewater

Location/Project:

Biannual Indust. Compliance Monitoring

Client Sample ID:

Effluent Comp

Flag Definitions

Report Date:

Date Arrived:

Sampled By:

Date Sampled:

B = Below Regulatory Minimum H = Above Regulatory Maximum

MRL = Method Reporting Limit

6/25/01

5/23/01

5/23/01

MLR

M = Matrix Interference

Time Sampled: 9:36 AM

\* = Less Than Reporting Limit

#### Comments:

\*\*Field Data: pH=7.8, Temp=72.0 °F, Conductivity=9400us/cm.

Method	Parameter	Result	Units	Flag	MRL	Analysis Date
EPA 200.7	Copper Total	< MRL	mg/L	*	0.009	6/14/01
EPA 200.7	Nickel Total	< MRL	mg/L	*	0.02	6/14/01
EPA 200.7	Zinc Total	0.06	mg/L		0.04	6/14/01
EPA 200.9	Arsenic Total	0.036	mg/L		0.004	6/12/01
EPA 200.9	Cadmium Total	< MRL	mg/L	*	0.0006	6/19/01
EPA 200.9	Lead Total	< MRL	mg/L	*	0.004	6/21/01
EPA 200.9	Selenium Total	< MRL	mg/L	* M	0.004	6/22/01
EPA 200.9	Silver Total	< MRL	mg/L	*	0.0002	6/15/01
EPA 245.1	Mercury	< MRL	mg/L	*	0.0002	5/29/01
SM 2540-D	Total Suspended Solids	41	mg/L		8.3	5/25/01
SM 5210-B	Biochemical Oxygen Demand	310	mg/L		6.0	5/23/01
SM 5220-C	Chemical Oxygen Demand	660	mg/L		25	5/24/01
SM4500-NH3-E	Ammonia-N	29	mg/L		1	5/24/01

Reported by Jeremy Nicoll

Fairbanks Chemistry Supervisor



### NORTHERN TESTING LABORATORIES, INC.

3330 INDUSTRIAL AVENUE 5761 SILVERADO WAY; UNIT N POUCH 340043 FAIRBANKS, ALASKA 99701 ANCHORAGE, ALASKA 99518 PRUDHOE BAY, ALASKA 99734 (907) 456-3116 • FAX 456-3125 (907) 349-1000 • FAX 349-1016 (907) 659-2145 • FAX 659-2146

Williams Alaska Petroleum

1100 H & H Lane North Pole, AK 99705

Attn: Dave Guinn

Client ID:

Effluent Grab

Client Project #:

Source:

NTL Lab#:

A172835 Wastewater

Sample Matrix: Comments: H

Biannual Industrial Compliance Monitoring

Report Date: 6/6/01 Date Arrived: 5/24/01 Sample Date: 5/23/01 Sample Time: 9:08 Collected By: MLR

\*\* Legend \*\*

MRL = Method Report Level
MCL = Max. Contaminant Level
B = Present In Method Blank
E = Estimated Value
M = Matrix Interference
H = Above MCL

H = Above MCL D = Lost To Dilution

Method	Parameter	Units	Result	MRL	Date Prepared	Date Analyzed
EPA 1664	<b>.</b>					
	Oil and Grease	mg/L	8.16	2.04	5/24/01	5/31/01
EPA 602						
	Benzene	ug/L	0.40	0.30		6/2/01
	Chlorobenzene	ug/L	<mrl< td=""><td>0.30</td><td></td><td></td></mrl<>	0.30		
	1,2-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	1,3-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	1,4-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	Ethylbenzene	ug/L	<mrl< td=""><td>0.20</td><td></td><td></td></mrl<>	0.20		
	Toluene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	m,p-Xylene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	o-Xylene	ug/L	<mrl< td=""><td>0.30</td><td></td><td></td></mrl<>	0.30		
	4-Bromofluorobenzene	% Recovery	107			



### NORTHERN TESTING LABORATORIES, INC

3330 INDUSTRIAL AVENUE 5761 SILVERADO WAY; UNIT N POUCH 340043 FAIRBANKS, ALASKA 99701 ANCHORAGE, ALASKA 99518 PRUDHOE BAY, ALASKA 99734 (907) 456-3116 • FAX 456-3125 (907) 349-1000 • FAX 349-1016 (907) 659-2145 • FAX 659-2146

Williams Alaska Petroleum

1100 H & H Lane North Pole, AK 99705

Attn: Dave Guinn

Client ID:

Travel Blank

Client Project #:

Source:

NTL Lab#: A172836 Sample Matrix: Water

Comments:

: Water
Biannual Industrial Compliance Monitoring

Report Date: 5/31/01 Date Arrived: 5/24/01 Sample Date: 5/22/01 Sample Time: 15:30 Collected By: MLR

\*\* Legend \*\*

MRL = Method Report Level
MCL = Max. Contaminant Level
B = Present In Method Blank
E = Estimated Value
M = Matrix Interference
H = Above MCL

D = Lost To Dilution

Method	Parameter	Units	Result	MRL	Date Prepared	Date Analyzed
EPA 602						
	Benzene	ug/L	<mrl< td=""><td>0.30</td><td></td><td>5/24/01</td></mrl<>	0.30		5/24/01
	Chlorobenzene	ug/L	<mrl< td=""><td>0.30</td><td></td><td></td></mrl<>	0.30		
	1,2-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	1,3-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	1,4-Dichlorobenzene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	Ethylbenzene	ug/L	<mrl< td=""><td>0.30</td><td></td><td></td></mrl<>	0.30		
	Toluene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	m,p-Xylene	ug/L	<mrl< td=""><td>0.50</td><td></td><td></td></mrl<>	0.50		
	o-Xylene	ug/L	<mrl< td=""><td>0.30</td><td></td><td></td></mrl<>	0.30		
	4-Bromofluorobenzene	% Recovery	99			



**建**集体

# NORTHERN TESTING LABORATORIES, INC. 330 INDUSTRIAL AVENUE FAIRBANKS, ALASKA 99701 (907) 456-3116 - FAX 456-3125 761 SILVERADO WAY; UNIT N ANCHORAGE, ALASKA 99518 (907) 349-1000 - FAX 349-1016

3330 INDUSTRIAL AVENUE 5761 SILVERADO WAY; UNIT N POUCH 340043 FAIRBANKS, ALASKA 99701 ANCHORAGE, ALASKA 99518 PRUDHOE BAY, ALASKA 99734

(907) 659-2145 • FAX 659-2146

### ANALYTICAL SERVICES ORDER AND CHAIN OF **CUSTODY FORM**

PLEASE PRINT CLEARLY & FIRMLY

Nο 26463

					14- 20400
Client name and address:	- Petroleun	Phone:	2-2054	NTL	Account Number:
1100 IT 9 IT LOUNG	•	FAX:			YMENT INFORMATION: . or Contract #:
Morth Pole, AK	99705	EMail:		Auth	norization#:
Contact: Dave Guin		PWS No:		Cash	h or check payable to NTL: dit Card: (Please call for phone order)
Reporting Format: XRegular		e Send result	s to ADEC:		Requested Analysis
Sampled by:	Project information	on:		- S	4. 第一
nek	bjunnual y	Tricestria	1 Compliance	Containers	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Comments: A Risults to		DΉ	7.8		1 C.
		<i>,</i> .	70,0%	Vumber of	35.55
Please include	-unittai	Cend.	9400 weform	umbe	1 6 6 3 4 7 6 8 4 7 6 8 4 7 6 8 8 4 7 6 8 8 4 7 6 8 8 4 7 6 8 8 4 7 6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
Client Sample ID:	Sample Date/Tim	e	: NTL ID#:	Ž	Prugoble frometh A.  Oil 9 Croccae  Rain, 755, C.C.D.  Annonic.  As, Ca. As, S. Cor.)  As, Ca. As, S. Cor.)  As, Ca. As, S. Cor.)
Effluent Arech	5/25/01	3 WW	0	4	3 /
Effhunt Cimp	5/23/01	34 WW	-20371de	5	2//
Travel Bruk	5/23/	e, DT	e	2	2
Refinquished by:	Date/Time: ///a	I .	418		To be completed by NTL
Relinquished by: 112	<u> </u>		U 5.23 OL		Sample Received: ANCFAI COC Seal Intact?YesNoN/A
Relinquished by: 川台 LMW 5タカウト	Date/Time:	Receive	id by:		
	Date/Time:	Receive	ed by:		Comments: N13, (21) 2173 NV 42504
					Temperature on Arrival: °C  Comments: Nas, Cao 21/42504  Pres Org 2301  LAND 52301  Nutris 21/100; PH22
Client Signature:					Nu tois of the
By signing, I have read and acc this form or as otherwise stipula	epted the terms and	d conditions ou	tlined on the back	of L	Page of
			Aut of paroliago of		· ~9~ <u>~~</u> ~·



#### North Pole Refinery - Laboratory 1100 H&H Avenue North Pole , Alaska 99705

Phone: (907) 488-0016 Fax: (907) 488-0016

#### ANALYTICAL REPORT

Sample Description:

WAPI Effluent

Date/Time Sampled:

5/23/01 5/23/01 900 1000

Lab Sample Number: Project Number:

Proponent:

ENVI 01-002

Dave Guinn

Sample Matrix:

Date/Time Received:

wastewater

Preservation:

none

Sample Details:

none

					Analysis
EPA Method	Parameter	Result	Units	MDL	Date
APHA 5210B	BOD	236	mg/L	6	5/23/01
APHA 2540D	TSS	50	mg/L	9	5/23/01
HACH 2-160	COD	640	mg/L	10	5/23/01
1664A	Oil and Grease	15.62	mg/L	3	5/24/01
7060A	Arsenic	33	ug/L(ppb)	5	6/7/01
7060A 6010B	Arsenic Cadmium	33 ND	ug/L(ppb) ug/L(ppb)	5 5	6/ <b>7</b> /01 6/ <b>7</b> /01
6010B	Cadmium	ND	ug/L(ppb)	5	6/7/01
6010B 7241	Cadmium Lead	ND ND	ug/L(ppb) ug/L(ppb)	5 2	6/ <b>7</b> /01 6/ <b>7</b> /01
6010B 7241 7740	Cadmium Lead Selenium	ND ND ND	ug/L(ppb) ug/L(ppb) ug/L(ppb)	5 2 5	6/7/01 6/7/01 6/7/01
6010B 7241 7740 6010B	Cadmium Lead Selenium Copper	ND ND ND ND	ug/L(ppb) ug/L(ppb) ug/L(ppb) ug/L(ppb)	5 2 5 10	6/7/01 6/7/01 6/7/01 6/7/01
6010B 7241 7740 6010B 6010B	Cadmium Lead Selenium Copper Nickel	ND ND ND ND ND	ug/L(ppb) ug/L(ppb) ug/L(ppb) ug/L(ppb) ug/L(ppb)	5 2 5 10 20	6/7/01 6/7/01 6/7/01 6/7/01 6/7/01

Analyst: Reviewer:

7/10/01